

HDMI сплиттер, 2 порта

DSP-2PH4-03

PERFECT CONNECTION

- Sends a single HDMI signal to 2 displays
- Signal amplifier Improves signal quality
- Perfect for home theatres, classand conference rooms



Особенности

- Разветвитель HDMI сигнала
- Разветвляет цифровой HDMI видео\аудио сигнал на 2 монитора, телевизора или плазменных экрана
- Цифровой широкополосный усилитель увеличивает дальность распространения сигнала, восстанавливая качество входного сигнала
- Поддержка 3D-видео

Упаковка

Кол-во в коробке, шт	45
Объем коробки, куб.м.	0.02738
Вес коробки, кг	3.79
Размеры индивидуальной упаковки ДхШхВ:	120x25x180 mm
Размеры картонной коробки ДхШхВ:	370x370x200 mm
Страна происхождения	CN
Баркод	8716309091442
Таможенный код	8517620000

Содержимое упаковки

Splitter
USB power cable
User manual

Спецификация

Ports: one input receptacle, 2 output HDMI output receptacles, 19 pin (A)
Interface standard: HDMI + HDCP v.1.4 (compatible with all HDMI versions)
Video formats: HDMI (480p/576i/576p/720p/1080i/1080P)
Maximal single-link range: 1920x1080 pixels, 1080p
Dual-link range: up to 3840x2160 at 30 Hz; color 30bit, 36bit

Supports Blue-Ray: 24/50/60fs/HD-DVD/xvYCC, audio DTS-HD/Dolby-trueHD/DTS/Dolby-AC3/DSD/HD(HBR)
Signal retiming support
Working distance: up to 20 m at AWG26 HDMI cable (at 4K resolution 8 m input max, up to 12 m output)

Сертификаты

