




FORCE 165 230V ACX PLASTIC CARRY CASE



Обзор

FORCE 165 230V ACX PLASTIC CARRY CASE

cod. 815857

MMA inverter, electrode welding machine in direct current (DC).

Usable electrodes: rutile, basic, stainless steel, cast iron, etc.

Features:

- Reduced weight and dimensions
- High welding current stability in spite of mains voltage fluctuations
- Arc force, hot start and anti-stick devices
- Thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator ($\pm 15\%$) protections.

Complete with MMA welding accessories and plastic carry case.



1 PH 230V



МАРКИРОВКА CE



СЕРТИФИКАЦИИ EAC

Технические данные

CODE	КОД 815857	A_{MAX}	МАКСИМАЛЬНЫЙ ПОГЛОЩЕННЫЙ ТОК 31 A	V_{1PH}	ОДНОФАЗНОЕ НАПРЯЖЕНИЕ СЕТИ 230 V
P_{MAX}	МАКС. ПОТРЕБЛЯЕМАЯ МОЩНОСТЬ 4,1 kW	IP	СТЕПЕНЬ ЗАЩИТЫ IP21	F	ЧАСТОТЫ СЕТИ 50 / 60 Hz
P_{GEN}	МИН. МОЩНОСТЬ ДВИГАТЕЛЯ-ГЕНЕРАТОРА 6 kW	W_H	РАЗМЕРЫ 38 x 42 x 17 cm	A_{MIN} / A_{MAX} / DC	ДИАПАЗОН РЕГУЛИРОВАНИЯ 10 - 150 A
	ПРЕДОХРАНИТЕЛЬ ДЛЯ СЕТИ 16 A	kg	ВЕС 5,5 kg	% USE_{20°C}	% USE (ИСПОЛЬЗОВАТЬ 20 ° C) 60% @ 150A %
η	ИСПОЛНЕНИЯ 82 V	BAR CODE	КОД EAN 800489778955 2	A_{MAX} 40°C DC	МАКСИМАЛЬНЫЙ ТОК DC (EN 60974-1) 140 @ 7% A
φ	КОЭФФИЦИЕНТ МОЩНОСТИ (cosphi) 0,6		ЧАСТЕЙ / ПАЛЛЕТ 36 pz/pallet	V₀ DC	МАКС. ХОЛОСТОЕ НАПРЯЖЕНИЕ 72 V



FORCE 165 230V ACX PLASTIC CARRY CASE



ДИАМ. ЭЛЕКТРОДОВ
ИСПОЛЬЗУЕМЫХ В DC 1,6 - 4 mm

(*)%USE:DATUM CREATED BY TELWIN,

Входящие в комплект аксессуары

null - 124508

null - 712250

null - 322800

null - 712257



null - 712030



null - 712260



null - 712139