



AUTOTRONIC 25 BOOST 230V 12V/24V



Обзор

AUTOTRONIC 25 BOOST 230V 12V/24V

cod. 807540

Battery charger with electronic control of the charging current, automatic interruption and restart (TRONIC), for charging lead-acid batteries with 12/24V voltage.

Fit with switches to choose either anormal charge (MIN) or quick charge (BOOST) in the buffer mode (TRONIC) or drooping characteristic mode (CHARGE).

The buffer automatic charge is adequate for maintenance free sealed batteries (GEL/AGM/START-STOP), while the drooping characteristic charge is adequate for free-electrolyte batteries (WET).

Features:

- choice of output voltage, type of charge, charging mode
- display of charging current
- protection against overloads and polarity reversal.



1 PH 230B



МАРКИРОВКА CE



СЕРТИФИКАЦИИ EAC

Технические данные

CODE	КОД 807540	A _{EFF}	ТОК ЭФФЕКТИВНОГО ЗАРЯДА 18 / 12 A	W/H/L	РАЗМЕРЫ 22,5 x 29 x 20,5 cm
V _{1PH}	ОДНОФАЗНОЕ НАПРЯЖЕНИЕ СЕТИ 230 V	A _{EN}	ТОК КОНВЕНЦИОНАЛЬНОГО ЗАРЯДА EN60335-2-29 12 / 8 A	kg	ВЕС 7,2 kg
F	ЧАСТОТЫ СЕТИ 50 / 60 Hz	C _{MIN}	МИН. НОМИНАЛЬНАЯ ССЫЛКА ПОТЕНЦИАЛ 30 / 20 A	BAR CODE	КОД EAN 800489764142 3



AUTOTRONIC 25 BOOST 230V 12V/24V



ПОГЛОЩЕННАЯ МОЩНОСТЬ ЗАРЯДА
300 W



МАКС. НОМИНАЛЬНАЯ ССЫЛКА
ПОТЕНЦИАЛ 225 / 180 A



ЧАСТЕЙ / ПАЛЛЕТ 56 pz/pallet



НАПРЯЖЕНИЕ ЗАРЯДКИ 12 / 24 V



РЕГУЛИРОВКА ПОЗИЦИИ 4



ЧАСТЕЙ / ПАЛЛЕТ - В 42 pz/pallet-B

Входящие в комплект аксессуары

null - 123985



null - 712623

null - 123986



null - 712624