



T-CHARGE 2012V/24V



NEW

Обзор

T-CHARGE 2012V/24V

cod. 807594

Multi-functional electronic battery charger and trickle charger for WET, GEL, AGM, MF, PbCa, EFB, 12V/24V batteries.

Choice of 2 charging voltages in Pulse Tronic mode: 12V / 24V. Automatic choice of charging current.

Advanced functions for charging and maintenance of batteries at low temperatures and for AGM batteries. Activation of the RECOVERY function enables resetting of sulphated batteries.

Features:

- Automatic charge and maintenance in Pulse Tronic;
- 2 charging voltages;
- Led display of battery charge level;
- AGM function to charge and maintain AGM batteries;
- COLD function to charge and maintain batteries at low temperatures;
- RECOVERY function to recover sulphated batteries;
- SUPPLY function for stable power supply during battery changing;
- Protection against overcharge, short circuit and polarity reversal.

Complete with cable with clamps and cable with eyelets.



1 PH 230V



МАРКИРОВКА CE

Технические данные

CODE	КОД 807594	A_{EFF}	ТОК ЭФФЕКТИВНОГО ЗАРЯДА 8 / 4 А		РЕГУЛИРОВКА ПОЗИЦИИ АВТОМАТИС
V_{1PH}	ОДНОФАЗНОЕ НАПРЯЖЕНИЕ СЕТИ 230 V	A_{EN}	ТОК КОНВЕНЦИОНАЛЬНОГО ЗАРЯДА EN60335-2-29 8 / 4 А	IP	СТЕПЕНЬ ЗАЩИТЫ IP65
F	ЧАСТОТЫ СЕТИ 50 / 60 Hz	C_{MIN}	МИН. НОМИНАЛЬНАЯ ССЫЛКА ПОТЕНЦИАЛ 5 А		РАЗМЕРЫ 30 x 9,5 x 5,5 cm
P	ПОГЛОЩЕННАЯ МОЩНОСТЬ ЗАРЯДА 115 W	C_{MAX}	МАКС. НОМИНАЛЬНАЯ ССЫЛКА ПОТЕНЦИАЛ 180 А	kg	ВЕС 1,33 kg



T-CHARGE 2012V/24V



НАПРЯЖЕНИЕ ЗАРЯДКИ 12 / 24 V