



Product Data Sheet

RACING OIL SM 5W-50

Product Description:

RACING OIL SM 5W-50 is a high performance motor oil based on 100% synthetic technology with exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fuelled engines in passenger cars with or without turbocharger, working under severe temperature and load conditions.

RACING OIL SM 5W-50 is based on high quality synthetic base oil in combination with an unique additive package to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions..

RACING OIL SM 5W-50 exceeds the following performance criteria:

API SN ACEA A3/B4 MB 229.1 VW 502.00/505.00

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	5W-50
Density@15°C	kg/m ³	ASTM D4052	852
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	109
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	18.4
Viscosity Index		ASTM D2270	189
Viscosity CCS @-30°C, max	cP	ASTM D2270	6600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	10.2
Sulphated Ash	%Wt	ASTM D874	1.09

Product Nr: 4202

Date Issued: 15-01-2018

Date Superseded: 28-06-2010

Revision nr: 01