



Typical Inspection Data:

Density @ 20°C	0.839 g/cm ³
Viscosity @ 100°C	8.8 cSt
Viscosity @ 40°C	44 cSt
Viscosity Index	185
Viscosity CCS @ -35 °C	5100 cP
T.B.N.	9.1 mg KOH/g
Sulphated Ash Mass	0.7%
Zinc	0.09%
Calcium	0.11%
Phosphorus	0.07%
Colour	Amber
Flash Point	>200°C

Eco-V 0W-20

Fully Synthetic

Official Approvals:

Officially approved by Volvo to meet VCC RBS0-2AE

Recommended by Comma for applications requiring:

ACEA C5; API SN

Product Features:

- Fully synthetic engine oil specifically developed for latest technology Volvo engines from 2013 onwards.
- Designed for high fuel efficiency.
- Suitable for petrol and diesel vehicles.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

UPDATED: 08-06-2023