



Typical Inspection Data:

Density @ 20°C	0.847 g/cm ³
Viscosity @ 100°C	8.4 cSt
Viscosity @ 40°C	46 cSt
Viscosity Index	161
Viscosity CCS @ -30°C	3800 cP
T.B.N.	8.1 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.09%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

Eco-F 5W-20

Fully Synthetic

Official Approvals:

Verified by Jaguar Land Rover to meet the requirement of STJLR.03.5004

Recommended by Comma for applications requiring:

FORD WSS M2C948-B, WSS M2C948-A, WSS-M2C925-A, WSS-M2C925-B; ILSAC GF-5; ACEA C5; API SN, SN-RC

Product Features:

- Fully synthetic, high performance 5W-20 oil suitable for use in the latest Ford EcoBoost engines.
- To ensure correct oil selection check Comma's latest
- application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 21-06-2021