



X-Flow Type PD 5W-40

Fully Synthetic

Recommended by Comma for applications requiring:

VW 505 01; FORD WSS-M2C917-A
ACEA C3
API SL CF

Product Features:

- Fully synthetic 5W-40 oil for vehicles fitted with the VW 'Pumpe Düse' PD or unit injector engine.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20°C	0.850 g/cm ³
Viscosity @ 100°C	14.0 cSt
Viscosity @ 40°C	85 cSt
Viscosity Index	170
Viscosity CCS @ -30°C	6000 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.09%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

UPDATED: 07.05.2019